

DYNAMIC ENGINEERING

435 Park Dr., Ben Lomond, Calif. 95005
831-336-8891 Fax 831-336-3840
<http://www.dyneng.com>
sales@dyneng.com
Est. 1988

User Manual

PCIBPMC

PCI 1 Slot PMC Compatible Carrier

Revision D5
Corresponding Hardware: Revision D
Fab number 10-2002-0104

PCIBPMC
PCI and PMC Compatible Carrier

Dynamic Engineering
435 Park Drive
Ben Lomond, CA 95005
831-336-8891
831-336-3840 FAX

©2002-2004 by Dynamic Engineering.
Other trademarks and registered trademarks are owned by their
respective manufactures.
Manual Revision D5. Revised 8/23/04

This document contains information of proprietary interest to Dynamic Engineering. It has been supplied in confidence and the recipient, by accepting this material, agrees that the subject matter will not be copied or reproduced, in whole or in part, nor its contents revealed in any manner or to any person except to meet the purpose for which it was delivered.

Dynamic Engineering has made every effort to ensure that this manual is accurate and complete. Still, the company reserves the right to make improvements or changes in the product described in this document at any time and without notice. Furthermore, Dynamic Engineering assumes no liability arising out of the application or use of the device described herein.

The electronic equipment described herein generates, uses, and can radiate radio frequency energy. Operation of this equipment in a residential area is likely to cause radio interference, in which case the user, at his own expense, will be required to take whatever measures may be required to correct the interference.

Dynamic Engineering's products are not authorized for use as critical components in life support devices or systems without the express written approval of the president of Dynamic Engineering.

Connection of incompatible hardware is likely to cause serious damage.



Table of Contents

| | |
|---|-----------|
| PRODUCT DESCRIPTION | 5 |
| Shunt Settings | 6 |
| DipSwitch Settings | 7 |
| Reserved Pins Routing | 8 |
| Options | 8 |
| PMC Module Backplane IO Interface Pin Assignment | 10 |
| PMC Module Pn4 Ethernet and Serial Pin Assignment | 11 |
| APPLICATIONS GUIDE | 12 |
| Interfacing | 12 |
| Construction and Reliability | 13 |
| Thermal Considerations | 13 |
| WARRANTY AND REPAIR | 14 |
| Service Policy | 14 |
| Out of Warranty Repairs | 15 |
| For Service Contact: | 15 |
| SPECIFICATIONS | 16 |
| ORDER INFORMATION | 16 |



List of Figures

| | | |
|----------|--------------------------------|----|
| FIGURE 1 | PCIBPMC PN4 INTERFACE STANDARD | 10 |
| FIGURE 2 | PCIBPMC PN4 ETHERNET , SERIAL | 11 |



Product Description

PCIBPMC is part of the Dynamic Engineering PCI and PMC Compatible family of modular I/O components. The PCIBPMC adapts one PMC to one PCI slot.

Special features:

- Universal PCI 1/2 length card.
- LED on PMC Busmode "Present"
- LED on plus 12V
- LED on minus 12V
- LED on plus 5V
- LED on plus 3.3V
- Onboard 10A regulator for PMC 3.3V supply
- Selection switch for PCI3.3 or regulated 3.3
- User selectable secondary VIO.
- 32 or 64 bit operation on either bus
- 66 or 33 MHz operation. With 66 MHz. primary bus speed the secondary bus can be 66 or 33 MHz. Secondary bus can not be at a higher rate than the primary bus.
- Front panel connector access through PCI bracket
- User IO [Pn4] available through 2 cable connectors (DIN IDC and SCSI II compatible) Spare pins on SCSI connector can be jumpered to power or ground.
- Cooling cutout for increased airflow to PMC
- Optional Fan to increased airflow
- Optional Ethernet connectors to support PMCs with Ethernet
- Optional Serial Port connectors to support PMCs with Serial Ports
- JTAG programming support

The PCIBPMC is ready to use with the default settings. Just install the PMC onto the PCIBPMC and then into the system. There are a few settings which can optimize performance.



Shunt Settings

Select the appropriate VIO for your PMC. A PMC can be 3.3V or 5V or “universal”. Please select the 3.3 or 5V VIO choice with the shunt **J4**. The Voltage choices are marked. Install the shunt for 3.3V operation; open for 5V operation.

The VIO plane is a reference for the IO level. The specification does not prohibit larger current consumption from these pins. The PCIBPMC design utilizes a MOSFET to control the 5V or 3.3V rails onto the VIO plane. Max consumption on the VIO rail is 3A. The maximum power draw of a PMC is 7.5W leaving a large safety factor. [The factory setting is 3.3V on the secondary VIO rail.](#)

Select the 3.3V source for your PMC. Some backplanes have 3.3 and some do not. Sometimes the isolation provided by an inline power supply is useful. Sometimes there is not enough 3.3V to supply all of the devices and it is handy to convert some of the 5V rail to 3.3V. The PCIBPMC has a switching DC/DC power converter built in.

When shunt **J1** is installed the switching regulator is enabled and the backplane power path is disabled. The switching regulator controls a low impedance MOSFET to pass the 5V onto the 3.3V rail. When the switching regulator senses that the voltage is within tolerance the MOSFET is disabled. When the voltage falls below the threshold the MOSFET is enabled. An inductor and several large value tantalum capacitors are used to provide “clean” power to the PMC. The switching regulator is much more efficient than a linear regulator resulting in lower heat dissipation and a higher MTBF. When shunt J1 is **not** installed, the 3.3V rail from the backplane is routed to the PMC. [The factory setting is installed.](#)



DipSwitch Settings

Please note that the switch numbering and '1' and '0' definitions are per the silk screen.

Select the “green power” clock setting. With the new revision of the bridge [Intel 21154] the secondary clock can be set to be driven low or continue to operate when in the power down state. With the **DIP switch 1** set to '0' the clock will be driven low during power down and with the switch '1' the clock will always be driven. **The factory setting is '1'**. **BPCCE** is the signal controlled with switch 1.

Select the Bridge capability to run at 66 MHz. The bridge is 66 MHz capable and should be selected to operate in that mode with **DIP switch 2** in the '0' position. With switch 2 '1' switch 4 should also be '1'. **CONFIG66** is the signal controlled with switch number 2. **The factory setting is '0'**.

Select the secondary side [PMC] PCI bus frequency. The options are to use the PCI bus speed [primary] or to force 33 MHz on the secondary side. The PMC to be installed must be 66 MHz compliant to use the 66 MHz secondary side option. The speed is controlled with the **DIP switch #3** position. '0' = 66 MHz capable secondary side. '1' = 33 MHz. **SM66EN** is the signal name controlled by the switch. **The factory setting is '0'**.

The SM66EN signal is also routed to the PMC connector pin M66EN. If the PMC uses the M66EN as an input then the dipswitch can be used to control the frequency. If the PMC uses the M66EN pin as a control, then the Switch may have no effect. For example if the switch is in the '0' position and the PMC is selecting M66EN = '0' then the PMC will “win” and the signal will be at the 33 MHz setting. Both the dipswitch and the PMC M66EN have to be enabled for 66 MHz operation. *Please note that the '1' and '0' of the dipswitch are "human" interface not electrical interface.*

Select the primary PCI bus speed. With **DIP switch 4** = '0' = backplane termination = 66 MHz capable. '1' = force 33 Mhz. Operation. If the rest of the cards installed on the same PCI segment and the segment itself are 66 MHz capable then the PCI primary speed will be 66 MHz. If any device on the segment is set to 33 MHz only then the entire segment will operate at 33 MHz. We recommend enabling the 66 MHz operation and using the bridge to switch to 33 MHz for the PMC. **P_M66EN** is the signal controlled by the switch. If P_M66EN is detected low then SM66EN is forced low by the bridge independent of the switch setting. **The factory setting is '0'**.



The remaining 4 switch positions can be read in from the bridge via the configuration space registers. The switch bits 8-5 correspond to the GPIO bits 0-3. The bits can be used for any purpose – Card numbering etc. The GPIO bits are also connected to a test point strip. If the GPIO bits are to be used as outputs be sure that the corresponding switch is in the '0' position. The factory setting is '0000'

Interrupts from the PMC are connected from the PMC to the primary PCI bus. INTA through INTD are mapped directly to the primary bus segment. The IDSEL is AD20 [secondary PCI].

The PCI reserved signals are routed to the PMC reserved pins in accordance with the PMC specification to allow for future signal definitions or special user signaling.

Reserved Pins Routing

| PCI | PMC |
|-----|--------|
| A9 | Pn2-8 |
| B10 | Pn2-9 |
| A11 | Pn2-10 |
| B14 | Pn1-10 |
| A40 | Pn1-41 |
| A41 | Pn1-42 |
| B63 | Pn3-1 |
| A92 | Pn3-59 |
| B92 | Pn3-63 |
| B93 | Pn3-61 |
| A94 | Pn3-64 |

Jumper and switch options are clearly marked in the component side silk screen.

Options

Dynamic Engineering offers two versions of the PCIxPMC design.

PCI2PMC is a passive implementation. The PCI connections on the PCI2PMC are longer and can limit the number of cards or adapters on a particular bus segment. The passive design has "0" delay between the primary PCI bus and the PMC. The VIO and bus speed definitions are common to the primary PCI bus and PMC.

PCIBPMC is bridged, isolating the PMC from the PCI bus. PCI connections



are specification compliant on the PCIBPMC. PCIBPMC can be used in multiple slots on the same PCI bus segment. The bridged design has pipeline delays between the primary and PMC buses. The bridged design has independent VIO definitions between the PMC and the primary bus.

In addition to the basic bridged or not bridged versions there are options for Ethernet, Fan, Serial ports, and minimization.

The PCIBPMC features a cooling cutout designed to support the addition of a fan in one of two positions. On PrPMC's and other PMCs with high thermal loads the fan option is a good idea. On cards with a lower thermal profile the fan is not needed. The fan produces 8 CFM in a small area to create a high LFM rating suitable for most cooling requirements. The fan used has a relatively low noise rating for quiet operation. Position 1 is closest to the PCI bezel and position 2 is shown below.

Some PMCs support ethernet connections over the Pn4 connector with pins specified by the PICMG standard 2.15. PCIBPMC supports ethernet capable cards with an optional two position RJ45 connector on the rear edge of the card.

Some PMCs support serial channels on Pn4 with pins specified by by PICMG standard 2.15. PCIBPMC supports serial capable cards with an optional pair of DB9F connectors on the rear edge of the card.

Please mix and match options as you need them.



PMC Module Backplane IO Interface Pin Assignment

The figure below gives the pin assignments for the PMC Module IO Interface - f PCIBPMC connectors. Also see the User Manual for your PMC board for more infor

| DIN IDC [P3] | | SCSI II [P2] | | Pn4 | |
|--------------|-----|--------------|----|--|----|
| C1 | A1 | 1 | 35 | 1 | 2 |
| C2 | A2 | 2 | 36 | 3 | 4 |
| C3 | A3 | 3 | 37 | 5 | 6 |
| C4 | A4 | 4 | 38 | 7 | 8 |
| C5 | A5 | 5 | 39 | 9 | 10 |
| C6 | A6 | 6 | 40 | 11 | 12 |
| C7 | A7 | 7 | 41 | 13 | 14 |
| C8 | A8 | 8 | 42 | 15 | 16 |
| C9 | A9 | 9 | 43 | 17 | 18 |
| C10 | A10 | 10 | 44 | 19 | 20 |
| C11 | A11 | 11 | 45 | 21 | 22 |
| C12 | A12 | 12 | 46 | 23 | 24 |
| C13 | A13 | 13 | 47 | 25 | 26 |
| C14 | A14 | 14 | 48 | 27 | 28 |
| C15 | A15 | 15 | 49 | 29 | 30 |
| C16 | A16 | 16 | 50 | 31 | 32 |
| C17 | A17 | 17 | 51 | 33 | 34 |
| C18 | A18 | 18 | 52 | 35 | 36 |
| C19 | A19 | 19 | 53 | 37 | 38 |
| C20 | A20 | 20 | 54 | 39 | 40 |
| C21 | A21 | 21 | 55 | 41 | 42 |
| C22 | A22 | 22 | 56 | 43 | 44 |
| C23 | A23 | 23 | 57 | 45 | 46 |
| C24 | A24 | 24 | 58 | 47 | 48 |
| C25 | A25 | 25 | 59 | 49 | 50 |
| C26 | A26 | 26 | 60 | 51 | 52 |
| C27 | A27 | 27 | 61 | 53 | 54 |
| C28 | A28 | 28 | 62 | 55 | 56 |
| C29 | A29 | 29 | 63 | 57 | 58 |
| C30 | A30 | 30 | 64 | 59 | 60 |
| C31 | A31 | 31 | 65 | 61 | 62 |
| C32 | A32 | 32 | 66 | 63 | 64 |
| | | 33 | 67 | Open, +5 or GND via J2 silk screen defined | |
| | | 34 | 68 | Open, +5 or GND via J3 | |

FIGURE 1

PCIBPMC PN4 INTERFACE STANDARD

Read table:

P3-C1 = P2-1 = Pn4-1

P3-A1 = P2-35 = Pn4-2

etc.



PMC Module Pn4 Ethernet and Serial Pin Assignment

| Ethernet[J6] | | Serial[J7,J8] | Pn4 | |
|--------------|----|---------------|-----|----|
| 11 | 14 | | 1 | 2 |
| 12 | 15 | | 3 | 4 |
| | | | 5 | 6 |
| 13 | 17 | | 7 | 8 |
| 16 | 18 | | 9 | 10 |
| | | | 11 | 12 |
| 21 | 24 | | 13 | 14 |
| 22 | 25 | | 15 | 16 |
| | | | 17 | 18 |
| 23 | 27 | | 19 | 20 |
| 26 | 28 | | 21 | 22 |
| | | | 23 | 24 |
| | | | 25 | 26 |
| | | 13 | 27 | 28 |
| | | 23 | 29 | 30 |
| | | | 31 | 32 |
| | | 12 | 33 | 34 |
| | | 22 | 35 | 36 |
| | | | 37 | 38 |
| | | | 39 | 40 |
| | | | 41 | 42 |
| | | | 43 | 44 |
| | | | 45 | 46 |
| | | | 47 | 48 |
| | | | 49 | 50 |
| | | | 51 | 52 |
| | | | 53 | 54 |
| | | | 55 | 56 |
| | | | 57 | 58 |
| | | | 59 | 60 |
| | | | 61 | 62 |
| | | | 63 | 64 |

FIGURE 2

PCIBPMC PN4 ETHERNET , SERIAL

The channel number is shown then the pin number. For example On the ethernet connector J6, there are two RJ45 connectors. Port 1 pin 1 is tied to Pn4 pin 1, Port 2 pin 8 is tied to pin 22 of Pn4.



Applications Guide

Interfacing

Some general interfacing guidelines are presented below. Do not hesitate to contact the factory if you need more assistance.

Installation

The PMC is mounted to the PCIBPMC prior to installation within the chassis. For best results: with the PCI bracket installed, install the PMC at an angle so that the PMC front panel bezel penetrates the PCI bracket then rotate down to mate with the PMC [PnX] connectors.

There are four mounting locations. Two into the PMC mounting bezel and two for the standoffs near the PMC bus connectors.

Start-up

Make sure that the "system" can see your hardware before trying to access it. Many BIOS will display the PCI devices found at boot up on a "splash screen" with the VendorID and CardId for the PMC installed and an interrupt level. Look quickly! If the information is not available from the BIOS then a third party PCI device cataloging tool will be helpful

Watch the system grounds. All electrically connected equipment should have a fail-safe common ground that is large enough to handle all current loads without affecting noise immunity. Power supplies and power consuming loads should all have their own ground wires back to a common point.

Power all system power supplies from one switch. Connecting external voltage to the PCIBPMC when it is not powered can damage it, as well as the rest of the host system. This problem may be avoided by turning all power supplies on and off at the same time. This applies more to the PMC installed into the PCIBPMC than the PCIBPMC itself, and it is smart system design when it can be achieved.

Construction and Reliability



The PCBPMC is constructed out of 0.062 inch thick FR4 material. A cooling cutout has been designed into the product for improved air flow to the PMC. The components on the PCBPMC are tied into the internal power planes to spread the dissipated heat out over a larger area. This is an effective cooling technique in the situation where a large portion of the board has little or no power dissipation.

A fan option is available for high thermal load PMCs or for chassis with a lack of air circulation.

Surface mounted components are used. The connectors are SMT for the PMC bus and through hole for the IO.

The PMC Module connectors are keyed and shrouded with Gold plated pins on both plugs and receptacles. They are rated at 1 Amp per pin, 100 insertion cycles minimum. These connectors make consistent, correct insertion easy and reliable.

The PMC Module is secured against the carrier with the PMC connectors. It is recommended, for enhanced security against vibration, that the PMC mounting screws are installed. The screws are supplied with the PMC from the OEM. Dynamic Engineering has screws, standoffs, blank bezels and other PMC hardware available at a reasonable cost if your PMC was not shipped with some of the require attachment hardware or if it has been misplaced.

Thermal Considerations

If the PMC installed has a high heat dissipation then forced air cooling is recommended.



Warranty and Repair

Dynamic Engineering warrants this product to be free from defects in workmanship and materials under normal use and service and in its original, unmodified condition, for a period of one year from the time of purchase. If the product is found to be defective within the terms of this warranty, Dynamic Engineering's sole responsibility shall be to repair, or at Dynamic Engineering's sole option to replace, the defective product. The product must be returned by the original customer, insured, and shipped prepaid to Dynamic Engineering. All replaced products become the sole property of Dynamic Engineering.

Dynamic Engineering's warranty of and liability for defective products is limited to that set forth herein. Dynamic Engineering disclaims and excludes all other product warranties and product liability, expressed or implied, including but not limited to any implied warranties of merchandisability or fitness for a particular purpose or use, liability for negligence in manufacture or shipment of product, liability for injury to persons or property, or for any incidental or consequential damages.

Dynamic Engineering's products are not authorized for use as critical components in life support devices or systems without the express written approval of the president of Dynamic Engineering.

Service Policy

Before returning a product for repair, verify as well as possible that the suspected unit is at fault. Then call the Customer Service Department for a RETURN MATERIAL AUTHORIZATION (RMA) number. Carefully package the unit, in the original shipping carton if this is available, and ship prepaid and insured with the RMA number clearly written on the outside of the package. Include a return address and the telephone number of a technical contact. For out-of-warranty repairs, a purchase order for repair charges must accompany the return. Dynamic Engineering will not be responsible for damages due to improper packaging of returned items. For service on Dynamic Engineering Products not purchased directly from Dynamic Engineering contact your reseller. Products returned to Dynamic Engineering for repair by other than the original customer will be treated as out-of-warranty.



Out of Warranty Repairs

Out of warranty repairs will be billed on a material and labor basis. The current minimum repair charge is \$100. Customer approval will be obtained before repairing any item if the repair charges will exceed one half of the quantity one list price for that unit. Return transportation and insurance will be billed as part of the repair and is in addition to the minimum charge.

For Service Contact:

Customer Service Department
Dynamic Engineering
435 Park Dr.
Ben Lomond, CA 95005
831-336-8891
831-336-3840 fax
InterNet Address support@dyneng.com



Specifications

| | |
|----------------------|--|
| Logic Interfaces: | PCI Interface 33/32 <-> 66/64 |
| Access types: | PCI bus accesses |
| CLK rates supported: | 33 or 66 MHz @ 100ns clock rates |
| Software Interface: | transparent Bridge. eg. i2154s in configuration space |
| Initialization: | switch selections for VIO, 3.3V source, primary and secondary and cable options |
| Interface: | PMC front bezel via PCI bracket and User IO connector via and or SCSI II connector |
| Dimensions: | 1/2 length PCI board. |
| Construction: | FR4 Multi-Layer Printed Circuit, Through Hole and Surface Components. |

Order Information

standard temperature range 0-70°C

PCIBPMC

1/2 length PCI card with PMC position
-FAN1/2 [fan installed in position 1 or 2]
-SER [serial ports installed]
-ENET [ethernet connectors installed]
<http://www.dyneng.com/pciBpmc.html>

HDEterm68

<http://www.dyneng.com/HDEterm68.html>
68 pin SCSI II to 68 screw terminal
converter with DIN rail mounting.

All information provided is Copyright Dynamic Engineering

