

DYNAMIC ENGINEERING

150 DuBois St. Suite C, Calif. 95060

831-457-8891 Fax 831-457-4793

<http://www.dyneng.com>

sales@dyneng.com


Est. 1988

PCI2cPCI-XXX

User Manual

Adapter for cPCI to PCI slot

Models: -32, -32-IO, -64 bit PCI



cPCI-32 model shown

Key Features

Plug and Play operation

32/64 bit PCI bus supported

J2 IO connections supported on -IO version

Manual Revision A2

Corresponding Hardware: Revision 01

Fab Number 10-2016-3001



PCI2cPCI-XXX

Dynamic Engineering
150 DuBois St Suite C
Santa Cruz, CA 95060

This document contains information of proprietary interest to Dynamic Engineering. It has been supplied in confidence and the recipient, by accepting this material, agrees that the subject matter will not be copied or reproduced, in whole or in part, nor its contents revealed in any manner or to any person except to meet the purpose for which it was delivered.

Dynamic Engineering has made every effort to ensure that this manual is accurate and complete. Still, the company reserves the right to make improvements or changes in the product described in this document at any time and without notice. Furthermore, Dynamic Engineering assumes no liability arising out of the application or use of the device described herein.

The electronic equipment described herein generates, uses, and can radiate radio frequency energy. Operation of this equipment in a residential area is likely to cause radio interference, in which case the user, at his own expense, will be required to take whatever measures may be required to correct the interference.

Dynamic Engineering's products are not authorized for use as critical components in life support devices or systems without the express written approval of the president of Dynamic Engineering.

This product has been designed to operate with cPCI Modules and compatible user-provided equipment. Connection of incompatible hardware is likely to cause serious damage.

©2016-2018 by Dynamic Engineering.

Other trademarks and registered trademarks are owned by their respective manufactures.

Revised 6/13/18



Table of Contents

PRODUCT DESCRIPTION	4
IO Pin Assignment	5
PMC Reference	8
Construction and Reliability	10
Thermal Considerations	10
WARRANTY AND REPAIR	11
Service Policy	11
Out of Warranty Repairs	11
For Service Contact:	11
SPECIFICATIONS	12
ORDER INFORMATION	13

List of Figures

FIGURE 1	SIGNAL TO HEADER ASSIGNMENT	7
FIGURE 2	PMC TO HDR ASSIGNMENT	9

Product Description

PCI2cPCI-32, PCI2cPCI-64, and PCI2cPCI-32-IO are related products used to adapt cPCI hardware into a PCI computer slot.

The first two models [-32 and -64] are for 32 and 64 bit cPCI models respectively. Both provide the PCI bus to the cPCI card installed. With the 32 bit model J1/P1 is supported. With the 64 bit model J1/P1 & J2/P2 are supported with J2/P2 covering the upper half of the PCI bus.

The -32-IO model has both connectors and J2/P2 covers the “rear IO” capability from the installed cPCI device. The cPCI IO connections are routed to two 50 pin headers [J1 & J2] and 4 additional bits on a 4 pin header J3. Suitable for carriers of PMC, IP models and standard rear IO cPCI-32 boards.

The connector table is best used as follows: determine which pin is used by the cPCI on J2 – this would mean looking at the cPCI design and [if present] the mezzanine and flowing through to the J2 connector. On the table find the pin on the header.

If you happen to use IP Modules the J1 and J2 connectors map directly into the rear IO specification for IP Modules. For PMC modules the IO will be spread across both J1 and J2 and potentially on J3 depending on the module.

Standard Ribbon cable and HDEterm50 can make an easy breakout for the rear IO.



IO Pin Assignment

Signal	Header Pin	cPCI Pin
A61	J3.1	P2.E1
A62	J3.2	P2.D1
A63	J3.3	P2.C1
A64	J3.4	P2.B1
IOA_1	J1.1	P2.A11
IOA_2	J1.2	P2.B11
IOA_3	J1.3	P2.C11
IOA_4	J1.4	P2.D11
IOA_5	J1.5	P2.E11
IOA_6	J1.6	P2.A10
IOA_7	J1.7	P2.B10
IOA_8	J1.8	P2.C10
IOA_9	J1.9	P2.D10
IOA_10	J1.10	P2.E10
IOA_11	J1.11	P2.A9
IOA_12	J1.12	P2.B9
IOA_13	J1.13	P2.C9
IOA_14	J1.14	P2.D9
IOA_15	J1.15	P2.E9
IOA_16	J1.16	P2.A8
IOA_17	J1.17	P2.B8
IOA_18	J1.18	P2.C8
IOA_19	J1.19	P2.D8
IOA_20	J1.20	P2.E8
IOA_21	J1.21	P2.A7
IOA_22	J1.22	P2.B7
IOA_23	J1.23	P2.C7
IOA_24	J1.24	P2.D7
IOA_25	J1.25	P2.E7
IOA_26	J1.26	P2.A6
IOA_27	J1.27	P2.B6
IOA_28	J1.28	P2.C6
IOA_29	J1.29	P2.D6
IOA_30	J1.30	P2.E6
IOA_31	J1.31	P2.A5
IOA_32	J1.32	P2.B5
IOA_33	J1.33	P2.C5
IOA_34	J1.34	P2.D5

IOA_35	J1.35	P2.E5
IOA_36	J1.36	P2.A4
IOA_37	J1.37	P2.B4
IOA_38	J1.38	P2.C4
IOA_39	J1.39	P2.D4
IOA_40	J1.40	P2.E4
IOA_41	J1.41	P2.A3
IOA_42	J1.42	P2.B3
IOA_43	J1.43	P2.C3
IOA_44	J1.44	P2.D3
IOA_45	J1.45	P2.E3
IOA_46	J1.46	P2.A2
IOA_47	J1.47	P2.B2
IOA_48	J1.48	P2.C2
IOA_49	J1.49	P2.D2
IOA_50	J1.50	P2.E2

IOB_1	J2.1	P2.A21
IOB_2	J2.2	P2.B21
IOB_3	J2.3	P2.C21
IOB_4	J2.4	P2.D21
IOB_5	J2.5	P2.E21
IOB_6	J2.6	P2.A20
IOB_7	J2.7	P2.B20
IOB_8	J2.8	P2.C20
IOB_9	J2.9	P2.D20
IOB_10	J2.10	P2.E20
IOB_11	J2.11	P2.A19
IOB_12	J2.12	P2.B19
IOB_13	J2.13	P2.C19
IOB_14	J2.14	P2.D19
IOB_15	J2.15	P2.E19
IOB_16	J2.16	P2.A18
IOB_17	J2.17	P2.B18
IOB_18	J2.18	P2.C18
IOB_19	J2.19	P2.D18
IOB_20	J2.20	P2.E18
IOB_21	J2.21	P2.A17
IOB_22	J2.22	P2.B17
IOB_23	J2.23	P2.C17
IOB_24	J2.24	P2.D17

IOB_25	J2.25	P2.E17
IOB_26	J2.26	P2.A16
IOB_27	J2.27	P2.B16
IOB_28	J2.28	P2.C16
IOB_29	J2.29	P2.D16
IOB_30	J2.30	P2.E16
IOB_31	J2.31	P2.A15
IOB_32	J2.32	P2.B15
IOB_33	J2.33	P2.C15
IOB_34	J2.34	P2.D15
IOB_35	J2.35	P2.E15
IOB_36	J2.36	P2.A14
IOB_37	J2.37	P2.B14
IOB_38	J2.38	P2.C14
IOB_39	J2.39	P2.D14
IOB_40	J2.40	P2.E14
IOB_41	J2.41	P2.A13
IOB_42	J2.42	P2.B13
IOB_43	J2.43	P2.C13
IOB_44	J2.44	P2.D13
IOB_45	J2.45	P2.E13
IOB_46	J2.46	P2.A12
IOB_47	J2.47	P2.B12
IOB_48	J2.48	P2.C12
IOB_49	J2.49	P2.D12
IOB_50	J2.50	P2.E12

FIGURE 1

SIGNAL TO HEADER ASSIGNMENT

PMC Reference

PMC Name	New Signal Name	HDR	Pin
A1	IOB_45	J2	45
A2	IOB_44	J2	44
A3	IOB_43	J2	43
A4	IOB_42	J2	42
A5	IOB_41	J2	41
A6	IOB_50	J2	50
A7	IOB_49	J2	49
A8	IOB_48	J2	48
A9	IOB_47	J2	47
A10	IOB_46	J2	46
A11	IOA_5	J1	5
A12	IOA_4	J1	4
A13	IOA_3	J1	3
A14	IOA_2	J1	2
A15	IOA_1	J1	1
A16	IOA_10	J1	10
A17	IOA_9	J1	9
A18	IOA_8	J1	8
A19	IOA_7	J1	7
A20	IOA_6	J1	6
A21	IOA_15	J1	15
A22	IOA_14	J1	14
A23	IOA_13	J1	13
A24	IOA_12	J1	12
A25	IOA_11	J1	11
A26	IOA_20	J1	20
A27	IOA_19	J1	19
A28	IOA_18	J1	18
A29	IOA_17	J1	17
A30	IOA_16	J1	16
A31	IOA_25	J1	25
A32	IOA_24	J1	24
A33	IOA_23	J1	23
A34	IOA_22	J1	22
A35	IOA_21	J1	21

A36	IOA_30	J1	30
A37	IOA_29	J1	29
A38	IOA_28	J1	28
A39	IOA_27	J1	27
A40	IOA_26	J1	26
A41	IOA_35	J1	35
A42	IOA_34	J1	34
A43	IOA_33	J1	33
A44	IOA_32	J1	32
A45	IOA_31	J1	31
A46	IOA_40	J1	40
A47	IOA_39	J1	39
A48	IOA_38	J1	38
A49	IOA_37	J1	37
A50	IOA_36	J1	36
A51	IOA_45	J1	45
A52	IOA_44	J1	44
A53	IOA_43	J1	43
A54	IOA_42	J1	42
A55	IOA_41	J1	41
A56	IOA_50	J1	50
A57	IOA_49	J1	49
A58	IOA_48	J1	48
A59	IOA_47	J1	47
A60	IOA_46	J1	46
A61	IOA_61	J3	1
A62	IOA_62	J3	2
A63	IOA_63	J3	3
A64	IOA_64	J3	4

FIGURE 2

PMC TO HDR ASSIGNMENT

Construction and Reliability

PCI2cPCI-XX is constructed out of 0.062 inch thick high temperature ROHS compliant FR4 material.

Through hole and surface mounting of components are used. High insertion and removal forces are required, which assists in the retention of components.

Thermal Considerations

PCI2cPCI-XX is a passive design with very low thermal dissipation. The installed cPCI card will not be in a standard cPCI chassis when using these adapters. Adequate cooling should be provided to enhance your development experience.



Warranty and Repair

Please refer to the warranty page on our website for the current warranty offered and options.

<http://www.dyneng.com/warranty.html>

Service Policy

Before returning a product for repair, verify as well as possible that the suspected unit is at fault. Then call the Customer Service Department for a RETURN MATERIAL AUTHORIZATION (RMA) number. Carefully package the unit, in the original shipping carton if this is available, and ship prepaid and insured with the RMA number clearly written on the outside of the package. Include a return address and the telephone number of a technical contact. For out-of-warranty repairs, a purchase order for repair charges must accompany the return. Dynamic Engineering will not be responsible for damages due to improper packaging of returned items. For service on Dynamic Engineering Products not purchased directly from Dynamic Engineering contact your reseller. Products returned to Dynamic Engineering for repair by other than the original customer will be treated as out-of-warranty.

Out of Warranty Repairs

Out of warranty repairs will be billed on a material and labor basis. Customer approval will be obtained before repairing any item if the repair charges will exceed one half of the quantity one list price for that unit. Return transportation and insurance will be billed as part of the repair and is in addition to the minimum charge.

For Service Contact:

Customer Service Department
Dynamic Engineering
150 DuBois St. Suite C
Santa Cruz, CA 95060
831-457-8891
831-457-4793 fax
support@dyneng.com



Specifications

Logic Interfaces:	PCI Interface 32/64 bit, universal signaling
Access types:	All PCI supported
CLK rates supported:	33/66 MHz. PCI
Software Interface:	NA
Access Modes:	Standard PCI accesses
Access Time:	Passive design with “no” delay added to accesses.
Interrupt:	INTA-D are supported
DMA:	REQ/GNT signals connected through
Onboard Options:	-32, -32-IO, -64
Interface:	-IO model has 2 x 50 pin Header Connectors plus 4 pin header for complete rear IO availability.
Dimensions:	Minimized board – PCI-32 or PCI-64 in width.
Construction:	High Temp ROHS compliant FR4 Multi-Layer Printed Circuit, Through Hole.
Power:	All rails connected through with mini-planes (+12, -12, 5, 3.3, VIO, Gnd).
User	NA
Other LED	NA.
Slots	NA
Temperature Range	-40C ⇄ +85C Components Standard
Temperature Coefficient:	2.17 W/°C for uniform heat across adapter
MTBF	TBD



Order Information

Standard temperature range -40↔85°C

PCI2cPCI-32

<http://www.dyneng.com/PCI2cPCI.html>

32 bit PCI adapter for cPCI

PCI2cPCI-32-IO

<http://www.dyneng.com/PCI2cPCI.html>

32 bit PCI adapter for cPCI with rear IO support

PCI2cPCI-64

<http://www.dyneng.com/PCI2cPCI.html>

64 bit PCI adapter for cPCI

HDRterm50

<http://www.dyneng.com/HDRterm50.html>

50-pin header to 50 screw terminal converter with DIN rail mounting.

HDRcabl50

50 pin ribbon cable compatible with PCI5IP and HDRterm50. Various lengths off-the-shelf, and custom

All information provided is Copyright Dynamic Engineering

